

# **Technical Data Sheet**

## Bondloc B7772 Adhesive Spray

### **PRODUCT DESCRIPTION**

B7772 is an aerosol adhesive that does not contain any CFC's. It bonds a wide range of materials giving rapid bond formation and is economical in use.

#### **APPLICATIONS**

B7772 can be used on a variety of substrates including wood, concrete, stone, tiles, rubber, foam, metals, rigid plastic, polyethylene, canvas fabrics, cardboard, paper and cork. It is also idea for fixing polyethylene sheets, thermal insulation and for packaging applications such as palletising or case sealing. B7772 can be used for foam bonding, upholstery, automotive, carpets and trim.

#### **USEFUL NOTES**

- CFC Free
- Fast tack
- Foaming formula for low soak in
- Economical in use

#### **INSTRUCTIONS FOR USE**

- Shake before use, spray from 15-20cms away on to one or both surfaces.
- For one-way application let adhesive dry for 30 seconds until tacky, then press into position.
- For two-way application, spray both surfaces and allow to dry for 2-5 minutes before bonding.
- For temporary bonding, spray one surface and allow to dry for 2-5minutes before bonding.
- Excess adhesive can be removed with a solvent cleaner or white spirit.
- To prevent spray nozzle from blocking, at the end of each period of use turn can upside down and press nozzle until spray is clear of adhesive.

#### **STORAGE**

Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight.

Bondloc UK Ltd. Units 1 & 2 Bewdley Business Park Bewdley, Worcestershire DY12 2TZ, UK

+44 (0) 1299 269 269 sales@bondloc.co.uk PRECAUTIONS: This product and the auxiliary materials normally combined with it are capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Safety Data Sheets (SDS) for this and all other products being used are understood by all persons who will work with the product. Warranty: All products purchased from or supplied by Bondloc are subject to terms and conditions set out in the contract. Bondloc warrants only that its product will meet those specifications designated as such herein or in other publications. All other information supplied by Bondloc is consider accurate but are furnished upon the express condition the customer shall make its own assessment to determine the product's suitability for a particular purpose. Bondloc makes no other warranty, either express or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or product will not infringe any patent.

#### **TECHNICAL FEATURES**

Appearance	Clear
Odour	Mild
Contents	Synthetic rubber/resin
Application Temperature	5°C - 40°C
Drying Time	2-5 Minutes

#### **HEALTH & SAFETY**

This technical information sheet does not constitute a Safety Data Sheet (SDS). Before using this product ensure you have read and fully understood this products SDS.

#### **PACKAGING FORMAT**

Aerosol Can.....500ml